

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claims 1-10 (Canceled).

11. (Currently Amended) A manufacturing method of a liquid crystal display, comprising, in order, the following steps of:

providing a transparent electrode on a substrate to drive liquid crystal;  
providing columnar spacers on the transparent electrode; and  
providing an alignment layer on the entire substrate.

12. (Currently Amended) A manufacturing method of a liquid crystal display, comprising the steps of:

providing a transparent electrode on a substrate to drive liquid crystal;  
providing an alignment layer on the transparent electrode;  
rubbing the alignment layer; ~~and~~  
providing columnar spacers on the rubbed alignment layer; and  
combining the first substrate and a second substrate that is provided with (i)  
liquid crystal drive electrodes composed of reflection electrodes and transmission  
electrodes and (ii) an interlayer insulation layer on which the reflection electrodes are  
provided, so that the columnar spacers and the reflection electrodes are disposed  
opposite each other.

13. (Original) A manufacturing method of a liquid crystal display, comprising the steps of:

- providing a black matrix layer on a substrate;
- providing a color filter layer;
- providing apertures on the black matrix layer; and
- providing columnar spacers in the apertures, using the apertures as a mask.

14. (Original) The manufacturing method of a liquid crystal display as defined in claim 13, wherein

the columnar spacers are provided in the apertures by applying a photosensitive black material and illuminating the material from a side where the color filter layer is not provided.

15. (New) A manufacturing method of a liquid crystal display comprising:

- providing a transparent electrode on a first substrate to drive liquid crystal;
- providing columnar spacers on the transparent electrode;
- providing an alignment layer on the entire first substrate, and
- locating the first substrate and a second substrate, provided with a reflection section that reflects incident light and a transmission section that transmits incident light, to be disposed opposite each other, so that the columnar spacers on the first substrate come in contact with the reflection section on the second substrate.

16. (New) A manufacturing method of a liquid crystal display comprising:

- providing a transparent electrode on a first substrate to drive liquid crystal;

providing an alignment layer on the transparent electrode;  
rubbing the alignment layer;  
providing columnar spacers on the rubbed alignment layer, and  
locating the first substrate and a second substrate, provided with a reflection section that reflects incident light and a transmission section that transmits incident light, to be disposed opposite each other, so that the columnar spacers on the first substrate come in contact with the reflection section on the second substrate.